



SMOOTH N SLEEK SDN BHD

(Co. Reg. No: 321141-K) **ESTD. SINCE 1994**

UNIT 1-05-12, KRYSTAL POINT CORPORATE PARK, KRYSTAL POINT II,
LEBUH BUKIT KECIL 6, 11900 BAYAN LEPAS, PENANG, MALAYSIA.

TEL : (6)04-644 8029, 644 9029 FAX : (6)04-644 0107 E-mail : sales@snspcb.com

WEBSITE : www.snspcb.com

BONDING FILM – ORDER # 118-1875

This sheet of Bonding Film is 1.50" x 2.25" (3.8 x 5.7 cm) in size. It is the same dry adhesive film we apply to circuit frames. Works great when you need to repair lifted lands, pads and conductors without the need to use messy liquid adhesives.

Specifications

Overall Size	2.25" x 1.50" (57 x 38 mm)
Adhesive	Phenolic film adhesive .002" (.051 mm) thick.
Bonding Temperature	475°F +/- 25°F (246°C +/- 14°C)
Bonding Time	30 seconds
Peel Strength	Minimum 8 lbs/inch (1.43 kg/cm) after cure to FR-4 material.
Shelf Life	1 year minimum.
REACH	Bonding Film contains less than 0.1% by weight any substance listed as a very high concern in Article 59 of REACH.



Dry film adhesive used to bond lifted lands, pads and conductors.