

Material Safety Data Sheet

Section 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Revision Date: 12 March 2015

Product Name : Coloring Agent (All Colors)
Product Numbers: 1 tube: 118-19XX

DISTRIBUTOR : SMOOTH N SLEEK SDN BHD
UNIT 01-05-12, KRYSTAL POINT II, KRYSTAL POINT CORPORATE PARK.
1 LEBUH BUKIT KECIL 6, 11900 BAYAN LEPAS, PENANG, MALAYSIA.
PHONE : 6(04)-644-8029, FAX : 6(04)-644-0107

Emergency Response: For Chemical Emergency Spill, Leak, Fire, Exposure or Accident
CALL CHEMTREC (24 hrs) **Within U.S.A and Canada** **1-800-424-9300 CCN4877**
Outside U.S.A and Canada **+1-703-527-3887 (Collect Calls Accepted)**

HMIS Hazard Rating

Health : 1
Flammability : 1
Reactivity : 0

Section 2. COMPOSITION, INFORMATION OR INGREDIENTS

The components of this product are not considered to be hazardous as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

This product contains petroleum distillates which are exempt from special labeling by OSHA.
The OSHA PEL/ACGIH TWA for mineral oil mist is 5mg/M.

Section 3. HAZARD IDENTIFICATION

Emergency Overview: Amber viscous liquid or gel with an oleoresinous odor.

Symptoms of Overexposure

INHALATION: In poorly ventilated areas, vapors from the heated product may cause temporary dizziness, headache, nausea, vomiting and drowsiness.
EYES: Eye contact may cause irritation.
SKIN: Dermatitis may be aggravated by contact.
INGESTION: May cause local irritation of mouth, esophagus and stomach.

Section 4. FIRST AID MEASURES

INHALATION: If vapors from the heated product are inhaled, remove affected person to fresh air, restore breathing, consult a physician.
EYE CONTACT: Immediately flush eyes with water for at least 15 minutes, consult a physician.
SKIN CONTACT: Wash exposed skin with soap and water and remove contaminated clothes.
INGESTION: If ingested, don't induce vomiting, consult a physician.

Section 5. FIRE-FIGHTING MEASURES

Flash Point & Method: 230°F (C.O.C.)
Flammable Limits in Air (% by volume): Lower 1.1 Upper 6.0
Extinguishing Media: Dry Chemical, Carbon dioxide, Foam.
General Hazard: Closed containers should be cooled with water using fog nozzles to minimize internal pressures and explosion risk. Can form dense fumes when burning, producing CO, CO₂ and other oxides.
Fire Fighting Instructions: Fire fighting personnel should wear SCBA.
Hazardous Combustion Prod.: NA
Flammable Properties: OSHA Class III B Combustible liquid.

Material Safety Data Sheet

Section 6. ACCIDENTAL RELEASE MEASURES

SPILL: In case of spills, keep from sparks or open flames. Ventilate area. Avoid breathing of concentrated vapors. Use oil absorbents and sweep up with broom and shovel into proper disposal container.

Section 7. HANDLING AND STORAGE

STORAGE TEMPERATURE: Ambient
STORAGE PRESSURE: Atmospheric
GENERAL: Store in sealed containers away from excessive heat, open flame, sparks or strong oxidizing agents. Avoid contact and use adequate ventilation.

Section 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Wear splash-proof safety glasses or face shield as needed to minimize eye contact.
Respirator: Not required unless mist is generated while material is heated or handled, in which case, an approved organic vapor respirator with mist filter should be used. Adequate ventilation should also be provided during normal use to maintain concentrations below the specified exposure limits.
Skin Protection: For prolonged or repeated exposure use impervious gloves, aprons, long sleeve shirts/pants should also be worn to minimize exposure.
Other Recommended: In accordance with good industrial hygiene, wash hands with soap and water after working with material.

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

Flashpoint: 230 °F (C.O.C.)
Boiling Point : >450°F
Vapor Pressure(mmHg): < 0.1 mmhg @ 20 °C
Vapor Densit: >1 (Air = 1)
Solubility in Water: Insoluble
Specific Gravity: 0.9562
Lbs/Gal: 7.9718
% Volatile By Weight: Less than 11
Evaporation Rate (Butyl Acetate = 1) : <1
Appearance: Amber color,
Odor: Typical oleoresinous odor.
Physical State: Gel

These properties represent typical batches and are not specifications.

Section 10. STABILITY AND REACTIVITY

This product is chemically stable. Hazardous polymerization will not occur. Avoid strong oxidizing agents.

Section 11. TOXICOLOGICAL INFORMATION

RESULTS OF COMPONENT TOXICITY TEST PERFORMED: Information not available.
HUMAN EXPERIENCE: Information not available.

Material Safety Data Sheet

Section 12. ECOLOGICAL INFORMATION

FURTHER INFORMATION: Do not allow spills to enter sewers or storm drains. Contain spill immediately. Remove all sources of ignition and absorb with inert material such as sand or clay. Discharge to navigable waterways or shorelines resulting in a visible surface sheen are prohibited and reportable under Section 311 (b) (3) of the Federal Water Pollution Control Act. (See 40 CFR 110).

Section 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state, and local regulations.

Section 14. TRANSPORT INFORMATION

Do not transfer to unmarked containers. Non-Regulated under D.C.T.

Section 15. REGULATORY INFORMATION

EPA-SARA, Title III Section 313 (40 CFR 372):

EPA Toxic Substances Control Act (TSCA):

All components of this product are listed in the TSCA inventory.

Canadian Substance Inventory:

One or more of the components of this product do not appear in the Canadian substance inventory.

Section 16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, neither Smooth N Sleek Sdn Bhd nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.