



SMOOTH N SLEEK SDN BHD

(Co. Reg. No: 321141-K)

UNIT 1-05-12, KRYSTAL POINT CORPORATE PARK, KRYSTAL POINT II,
LEBUH BUKIT KECIL 6, 11900 BAYAN LEPAS, PENANG, MALAYSIA

TEL. NO: 6(04)-644 8029, 644 9029 FAX NO: 6(04)-644 0107

E-MAIL : sales@snspcb.com WEBSITE : www.snspcb.com

SDS – COLOR AGENT (ORDER # 118-19XX)

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	COLOR AGENT
Other Product Name(s)	118-1969, 118-1970, 118-1971, 118-1972, 118-1973, 118-1974, 118-1975, 118-1976, 118-1977, 118-1978, 118-1979, 118-1980.
Importer/Distributor	SMOOTH N SLEEK SDN BHD (Co. Reg. No: 321141-K) UNIT 1-05-12, KRYSTAL POINT CORPORATE PARK, KRYSTAL POINT II, LEBUH BUKIT KECIL 6, 11900 BAYAN LEPAS, PENANG, MALAYSIA TEL. NO: 6(04)-644 8029, 644 9029 FAX NO: 6(04)-644 0107 E-MAIL ADDRESS : sales@snspcb.com WEBSITE : www.snspcb.com
Emergency Telephone Number	For Chemical Emergency Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night Within USA and Canada: 1-800-424-9300 CCN4877 Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

HMIS Rating:

Health:	1
Flammability:	1
Reactivity:	0



SECTION 2. HAZARD IDENTIFICATION

Classifications:	Classification according to Regulation(EC)No1272/2008 Classifications applicable to the OSHA GHS Hazard Communication Standard (29CFR1910.1200)
Emergency Overview:	Amber viscous liquid or gel with an oleoresinous odor.
Symptoms of Overexposure	
Eyes:	Eye contact may cause irritation.
Inhalation:	In poorly ventilated areas, vapors from the heated product may cause temporary dizziness, headache, nausea, vomiting, and drowsiness.
Skin:	Dermatitis may be aggravated by contact.
Ingestion:	Ingestion may cause local irritation of mouth, esophagus and stomach.

SECTION 3. COMPOSITION, INFORMATION OR INGREDIENTS

The components of this product are not considered to be hazardous as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

This product contains petroleum distillates which are exempt from special labeling by OSHA.

The OSHA PEL/ACGIH TWA for mineral oil mist is 5mg/M.

SECTION 4. FIRST AID MEASURES

Inhalation:	If vapors from the heated product are inhaled, remove affected person to fresh air, restore breathing, consult a physician.
Eye Contact:	Immediately flush eyes with water for 15 minutes, consult a physician.
Skin Contact:	Wash exposed skin with soap and water and remove contaminated clothes.
Ingestion:	If ingested, do not induce vomiting, consult a physician.



SMOOTH N SLEEK SDN BHD

(Co. Reg. No: 321141-K)

UNIT 1-05-12, KRYSTAL POINT CORPORATE PARK, KRYSTAL POINT II,
LEBUH BUKIT KECIL 6, 11900 BAYAN LEPAS, PENANG, MALAYSIA
TEL. NO: 6(04)-644 8029, 644 9029 FAX NO: 6(04)-644 0107
E-MAIL : sales@snspcb.com WEBSITE : www.snspcb.com

SDS – COLOR AGENT (ORDER # 118-19XX)

SECTION 5. FIRE-FIGHTING MEASURES

Flash Point & Method:	230°F (C.O.C.).
Flammable Limits in Air (% by volume):	Lower 1.1 Upper 6.0
Extinguishing Media:	Dry Chemical, Carbon dioxide, Foam.
General Hazard:	Closed containers should be cooled with water using fog nozzles to minimize internal pressures and explosion risk. Can form dense fumes when burning, producing CO, CO ₂ other oxides. Fire fighting personnel should wear SCBA.
Flammable Properties:	OSHA Class III B Combustible liquid.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Spill:	In case of spills, keep from sparks or open flames. ventilate area. Avoid breathing of concentrated vapors. Use oil absorbents and sweep up with broom and shovel into proper disposal container.
---------------	---

SECTION 7. HANDLING AND STORAGE

General:	Store in sealed containers away from excessive heat, open flame, sparks or strong oxidizing agents. Avoid contact and use adequate ventilation.
-----------------	---

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection:	Wear splash-proof safety glasses or face shield as needed to minimize eye contact.
Respirator:	Not required unless mist is generated while material is heated or handled, in which case an approved organic vapor respirator with mist filter should be used. Adequate ventilation should also be provided during normal use to maintain concentrations below the specified exposure limits.
Skin Protection:	For prolonged or repeated exposure use impervious gloves, aprons, long sleeve shirts/pants should also be worn to minimize exposure.
Other Recommended:	In accordance with good industrial hygiene, wash hands with soap and water after working with material.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Flashpoint:	230 °F (C.O.C.)
Boiling Point:	>450°F
Vapor Pressure(mmHg):	< 0.1 mmhg @ 20 °C
Vapor Density:	>1 (Air = 1)
Solubility in Water:	Insoluble
Specific Gravity:	0.9562
Lbs/Gal:	7.9718
% Volatile By Weight:	Less than 11
Evaporation Rate:	<1 (Butyl Acetate = 1)
Appearance:	Amber color, typical oleoresinous odor.

These properties represent typical batches and are not specifications.

SECTION 10. STABILITY AND REACTIVITY

This product is chemically stable. Hazardous polymerization will not occur. Avoid strong oxidizing agents.
--

Section 11. TOXICOLOGICAL INFORMATION

Results of Component Toxicity Test Performed:	Information not available.
Human Experience:	Information not available



SMOOTH N SLEEK SDN BHD

(Co. Reg. No: 321141-K)

UNIT 1-05-12, KRYSTAL POINT CORPORATE PARK, KRYSTAL POINT II,
LEBUH BUKIT KECIL 6, 11900 BAYAN LEPAS, PENANG, MALAYSIA

TEL. NO: 6(04)-644 8029, 644 9029 FAX NO: 6(04)-644 0107

E-MAIL : sales@snspcb.com WEBSITE : www.snspcb.com

SDS – COLOR AGENT (ORDER # 118-19XX)

SECTION 12. ECOLOGICAL INFORMATION

Do not allow spills to enter sewers or storm drains. Contain spill immediately. remove all sources of ignition and absorb with inert material such as sand or clay. discharge to navigable waterways or shorelines resulting in a visible surface sheen are prohibited and reportable under section 311 (b) (3) of the federal water pollution control act. (see 40 CFR 110)

SECTION 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with federal, state, and local regulations.

SECTION 14. TRANSPORT INFORMATION

Do not transfer to unmarked containers. non-regulated under D.O.T.

SECTION 15. REGULATORY INFORMATION

EPA-SARA, Title III Section 313 (40 CFR 372):

EPA Toxic Substances Control Act (TSCA): All components of this product are listed in the TSCA inventory.

Canadian Substance Inventory: One or more of the components of this product do not appear in the Canadian substance inventory.

SECTION 16. OTHER INFORMATION

To the best of our knowledge, the information contained herein is accurate. However, neither Smooth N Sleek Sdn Bhd., nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.